



Main material and finish:
Black powder coated ZDC hinge, nickel-plated steel pin

Application:
Opening angle 180°

Model	Specification							Remarks
	A	B	C	D	E	F	G	
CL226-1	36	60	16.5	8.4	8	15	8	Countersunk hole, ZDC
CL226-1A	36	60	16.5	8.4	8	15	8	Screw embedded, ZDC
CL226-1B	36	60	16.5	8.4	8	15	8	Countersunk hole, stainless steel
CL226-2	30	50	12.5	6.3	6	11.5	6	Countersunk hole, ZDC
CL226-2A	30	50	Refer to detailed drawing		6	11.5	6	Screw embedded, ZDC
CL226-2C	30	50	Refer to detailed drawing		6	11.5	6	Step hole, ZDC
CL226-2S	30	50	12.5	6.3	6	11.5	6	Countersunk hole, PA
CL226-2B	30	50	12.5	6.3	6	11.5	6	Countersunk hole, stainless steel
CL226-3	25	40	10.2	5.3	5	9	4	Countersunk hole, ZDC
CL226-3A	25	40	10.2	5.3	5	9	4	Screw embedded, ZDC

Quarter Turn Locks
Compression Locks & Latches
Handle Locks
Rod Control Locks
Electronic Locks
Canopy Locks, Handles & Door Stay
Hinges
9 Fold Accessories
Sealing Profiles
Fan Filter
Panel Fasteners
Sleeve & Termination
Wiring Accessories
Connectors