



DC AXIAL FANS

Series 120 120×120×38mm A



Material:

Impeller & Frame Plastic (UL94V-0)

Lead Wires: UL 1007

AWG#24 or Equivalent

Impeller: 7 Blades

Rotational direction CCW view from impeller side

Mass: 255g

Quarter Turn Locks

Compression Locks & Latches

Handle Locks

Rod Control Locks

Electronic Locks

Canopy Locks, Handles & Door Stay

Hinges

9 Fold Accessories

Sealing Profiles

Fan Filter

Panel Fasteners

Sleeve & Termination

Wiring Accessories

Connectors

PART NO.	B.S	VDC	VDC	Amp	Watt	RPM	m ³ /H	CFM	mmH ₂ O	IN H ₂ O	dB-A
SA121238-L	B	12	7~13.2	0.48	5.77	2800	162.6	95.8	9.52	0.37	45.6
SA121238-M	B	12	7~13.2	0.62	7.44	3200	185.8	109.4	12.42	0.49	49.0
Sa121238-H	B	12	7~13.2	0.71	8.52	3600	212.6	125.2	17.72	0.70	51.1
SA121238-U	B	12	7~13.2	0.75	9.00	4000	232.3	136.8	19.42	0.76	53.1
SA121238-S	B	12	7~13.2	0.88	10.56	4500	259.2	152.7	20.60	0.81	55.7
SA241238-L	B	24	14~26.4	0.24	5.76	2800	162.6	95.8	9.52	0.37	45.6
SA241238-M	B	24	14~26.4	0.31	7.44	3200	185.8	109.4	12.42	0.49	49.0
SA241238-H	B	24	14~26.4	0.32	7.68	3600	212.6	125.2	17.72	0.70	51.1
SA241238-U	B	24	14~26.4	0.35	8.40	4000	232.3	136.8	19.42	0.76	53.1
SA241238-S	B	24	14~26.4	0.44	10.56	4500	259.2	152.7	20.60	0.81	55.7
SA241238-F	B	24	14~26.4	0.66	15.84	5000	292.8	172.4	22.76	0.90	58.0
SE481238-G	B	48	36~56.0	0.85	40.80	5200	407.7	240.0	31.38	1.24	65.0

