



DC AXIAL FANS

Series 172 172×150×51mm B



Material:
Impeller Plastic(UL94V-0),
Frame Aluminum

Lead Wires: UL 1007
AWG#22 or Equivalent

Impeller: 5 Blades
Rotational direction CCW
view from impeller side

Mass: 760g

Quarter Turn
Locks

Compression
Locks &
Latches

Handle
Locks

Rod Control
Locks

Electronic
Locks

Canopy Locks,
Handles &
Door Stay

Hinges

9 Fold
Accessories

Sealing
Profiles

Fan Filter

Panel
Fasteners

Sleeve &
Termination

Wiring
Accessories

Connectors

PART NO.	B.S	VDC	VDC	Amp	Watt	RPM	m ³ /H	CFM	mmH2O	IN H2O	dB-A
SB121751-M	B	12	7~13.2	1.48	17.76	3500	403.8	237.8	27.35	1.08	58.3
SB121751-H	B	12	7~13.2	2.40	28.80	4100	481.2	283.4	37.93	1.49	63.8
SB121751-U	B	12	7~13.2	3.84	46.08	4800	562.9	331.5	52.04	2.05	66.5
SB121751-S	B	12	7~13.2	4.84	58.08	5500	611.5	360.1	61.19	2.41	69.7
SB241751-M	B	24	14~26.4	0.74	17.76	3500	403.8	237.8	27.35	1.08	58.3
SB241751-H	B	24	14~26.4	1.20	28.80	4100	481.2	283.4	37.93	1.49	63.8
SB241751-U	B	24	14~26.4	1.92	46.08	4800	562.9	331.5	52.04	2.05	66.5
SB241751-S	B	24	14~26.4	2.42	58.08	5500	611.5	360.1	61.19	2.41	69.7
SB481751-M	B	48	36~56	0.37	17.76	3500	403.8	237.8	27.35	1.08	58.3
SB481751-H	B	48	36~56	0.60	28.80	4100	481.2	283.4	37.93	1.49	63.8
SB481751-U	B	48	36~56	0.96	46.08	4800	562.9	331.5	52.04	2.05	66.5
SB481751-S	B	48	36~56	1.21	58.08	5500	611.5	360.1	61.19	2.41	69.7

