



Nylon Cable Gland



Material: Polyamide, sealing: modified rubber
 Color: Grey white (RAL 7035) Black (RAL 9005)
 Protection degree : Using suitable O-sealing within the clamping range it protection degree can reach Ip68
 Temperature Range : Min-40°C, Max 100°C, Short-term 120°C
 Properties : V2 (UL 94), free of halogen, phosphor and cadmium, passed RoHS UV-resistance, ageing - resistance certificates

HSK-P PG Thread

Article no. Grey	Article no. Black	Thread Dimension	Clamping range mm	AG mm	GL mm	Wrench size mm	Packet units
HSK-P07G	HSK-P07B	PG7	3~6.5	12.5	8	20	15
HSK-P09G-H	HSK-P09B-H	PG9	2.5~6	15.2	8	22	19
HSK-P09G	HSK-P09B	PG9	4~8	15.2	8	22	19
HSK-P11G	HSK-P11B	PG11	5~10	18.6	8	25	22
HSK-P13G-H	HSK-P13B-H	PG13.5	5~9	20.4	9	26.5	24
HSK-P13G	HSK-P13B	PG13.5	6~12	20.4	9	26.5	24
HSK-P16G-H	HSK-P16B-H	PG16	7~12	22.5	10	28	27
HSK-P16G	HSK-P16B	PG16	8~14	22.5	10	28	27
HSK-P21G-H	HSK-P21B-H	PG21	11~16	28.3	11	31.5	33
HSK-P21G	HSK-P21B	PG21	13~18	28.3	11	31.5	33
HSK-P29G-H	HSK-P29B-H	PG29	14~21	37	11	39	42
HSK-P29G	HSK-P29B	PG29	18~25	37	11	39	42
HSK-P36G	HSK-P36B	PG36	22~32	47	13	48.5	53
HSK-P42G	HSK-P42B	PG42	30~38	54	14	47.3	60
HSK-P48G	HSK-P48B	PG48	37~44	59.3	15	47	65

HSK-M Metric Thread

Article no. Grey	Article no. Black	Thread Dimension	Clamping range mm	AG mm	GL mm	Wrench size mm	Packet units
HSK-M12G	HSK-M12B	M12 X 1.5	3~6.5	12	8	20	15
HSK-M16G	HSK-M16B	M16 X 1.5	4~8	16	8	22	19
HSK-M20G	HSK-M2QB	M20 X 1.5	6~12	20	9	26.5	24
HSK-M25G	HSK-M25B	M25 X 1.5	13~18	25	11	31.5	33
HSK-M32G	HSK-M32B	M32 X 1.5	18~25	32	11	39	42
HSK-M40G	HSK-M4QB	M40 X 1.5	22~32	40	13	48.5	53
HSK-M50G	HSK-M50B	M50 X 1.5	30~38	50	14	47.3	60
HSK-M63G	HSK-M63B	M63 X 1.5	37~44	63	15	47	65

- Quarter Turn Locks
- Compression Locks & Latches
- Handle Locks
- Rod Control Locks
- Electronic Locks
- Canopy Locks, Handles & Door Stay
- Hinges
- 9 Fold Accessories
- Sealing Profiles
- Fan Filter
- Panel Fasteners
- Sleeve & Termination
- Wiring Accessories
- Connectors

