



DC AXIAL FANS

Series 120 120×120×25mm B



Material:

Impeller & Frame Plastic (UL94V-0)

Lead Wires: UL 1007

AWG#24 or Equivalent

Impeller: 7 Blades

Rotational direction CCW view from impeller side

Mass: 200g

Quarter Turn Locks

Compression Locks & Latches

Handle Locks

Rod Control Locks

Electronic Locks

Canopy Locks, Handles & Door Stay

Hinges

9 Fold Accessories

Sealing Profiles

Fan Filter

Panel Fasteners

Sleeve & Termination

Wiring Accessories

Connectors

PART NO.	B.S	VDC	VDC	Amp	Watt	RPM	m ³ /H	CFM	mmH2O	IN H2O	dB-A
SB121225-E	B	12	7~13.2	0.11	1.32	1500	100.84	59.39	1.82	0.07	31.0
SB121225-L	B	12	7~13.2	0.16	1.97	1900	126.85	74.70	2.73	0.11	36.1
SB121225-M	B	12	7~13.2	0.26	3.12	2200	144.44	85.07	3.47	0.14	40.3
SB121225-H	B	12	7~13.2	0.40	4.80	2500	175.65	103.44	5.38	0.21	44.7
SB241225-E	B	24	14~26.4	0.09	2.16	1500	100.84	59.39	1.82	0.07	31.0
SB241225-L	B	24	14~26.4	0.13	3.12	1900	126.85	74.70	2.73	0.11	36.1
SB241225-M	B	24	14~26.4	0.19	4.56	2200	144.44	85.07	3.47	0.14	40.3
SB241225-H	B	24	14~26.4	0.24	5.76	2500	175.65	103.44	5.38	0.21	44.7
SB481225-L	B	48	36~56	0.05	2.40	1500	100.84	59.39	1.82	0.07	31.0
SB481225-E	B	48	36~56	0.07	3.36	1900	126.85	74.70	2.73	0.11	36.1
SB481225-M	B	48	36~56	0.12	5.76	2200	144.44	85.07	3.47	0.14	40.3

